Dam ID:	HI00028	
Puu Ka	Ele	

Vulnerability Index:
Extreme High Moderate Low
1 2 3 4

Insped	ction No:
Date:	20 March 2006

STATE OF HAWAII - DLNR VISUAL DAM SAFETY INSPECTION SHEET

Persons Present		Affiliation	Affiliation					Phone Number		
D. K.	COE							-		
Gordon Chong		DLNR – Eng.								
		DLNR - DOFAV								
Sherile Faul		DLINK - DOI AV	V				_			
Weather Condition:		□ Rainy □ Drizz		•			, ,	•	•	
1. General: (Information	on currently on file undat	e as required)								
Dam/Res. Name	•	e as required)								
•	Walter Kortchak									
Owner Contact					Owne	Ph.				
Lessee					Lesse	e Ph.				
O & M Contractor					O & M	Ph.				
	Kilauea						22.18			
County	Kauai				Longit	ude _	159.40		° (decimal)	
Tax Map Key(s)										
Dam Status _		Hazard Potential	Н			Dam	Size <u>490</u>	ac.ft.		
Year Completed _	1890	Dam Length	1190		ft.	Dam	Height 2	5	ft.	
Normal Storage _	360 ac.ft.	Max. Storage			ac.ft.	Max.	Surface Ar	ea	ac.	
Offsite Drainage A	rea <u>mi.</u>	Spillway Type				Max.	. Spillway Q		cfs	
Owner owne land	ındar dam facility									
	under dam facility: Plan on file with the									
Reports on file with		Dopartinent.								

2.			ns for Owner's Rep.:				Comments
			ction Plans Available				
			acility Map				
			on & Maintenance Mar	nual 🗆			
		-	ncy Action Plan				
	Modifications / Improvements						
	Conduct Routine Inspections						
	Con	duc	t Routine Maintenance	· 🗆			
	Vehi	cle	access to site	Х			☐ Not accessible ☐ With Standard car X Requires 4-Wheel Drive
	Acce	ess	during heavy rains	Х			☐ Not accessible ☐ With Standard car X Requires 4-Wheel Drive
	Acce	ess	when spillway is flowing	ng x			☐ Not accessible ☐ With Standard car ☐ Requires 4-Wheel Drive
	Othe	er S	tudies Conducted				☐ Phase I ☐ Phase II ☐ Hydraulics ☐ Stability ☐ Hazard ☐ Seismic ☐ Other:
	Incid	lent	History				☐ Breached ☐ Overtop ☐ Slide ☐ Down stream Flooding ☐ Other:
	Res	ervo	oir's Current Use	х			☐ Sediment X Irrigation ☐ Recreation ☐ Flood Control ☐ Drinking Water
							☐ Power Generation ☐ Other:
			rs and Corrective Act		ıma	ntationa in	cluding Construction plans, specifications, improvements,
	Ш						Manuals and routine inspection logs for this dam facility.
			•				rith the department, submit any updates as applicable.
							Submit an updated EAP for this facility.
			· ·	_			lless of hazard class. Submit EAP if developed for the facility.
						•	letailing the improvements, modifications, and/or alterations at the
			dam site, unless cover				
			Routine inspection log			-	
	Χ	_	Dam owners shall pro			•	
	Χ		The dam did not appe				a regular basis.
			Access to site appears			•	
		•	or access provided.				Operational and emergency plans need to reflect this deficiency
			and emergency plans	need to	refle	ect this def	weather conditions and/or spillway overflows. Operational plans iciency or access provided.
			required to promptly a	dvise the	e de	partment o	esponses taken, and any damages incurred. Dam owners are of any sudden or unprecedented flood or unusual or alarming ersely affect the dam or reservoir.
		m.	Submit current Operat	tions and	d Ma	aintenance	Manual or Procedures for this dam / reservoir facility.
		n.	Submit Site or Facility controls and conduits.		this	Dam which	n identifies the location of major features including outlet works
		Ο.					
			nal Requirements:				
			llowing investigative stu ed Recommended	udy(s) a	re:		
	1760			Phase I S	Stuc	lv	
							ng □ Seepage □ Hydrology/Hydraulics □ EAP)
				Hydrolog	y ar	nd Hydraul	ics (including Probable Maximum Flood and spillway capacity)
				Stability			
				Seismic .			
				Hazard (Other:		sification	
		ш		Juioi			

Physical Dam Features: (Check All Applicable. Provide description of Items Observed and/or Take Photos. Indicate photo # in description.) 3. Reservoir: Level during inspection _____ft per _____ (gage / other) Normal Operating Level/Range ft per (gage / other) Description: Typical Operation ☐ Spillway always flowing x Kept within normal range ☐ Kept Empty ☐ Drained Daily ☐ Only filled by Storms □ # Observed: _____ Size: _____ by ____ in. Deep □ Not Visible Sinkhole in Res.: x None Observed Staff Gage: Findings: ☐ a. The reservoir was not inspected. b. The reservoir appeared to be in satisfactory condition, no corrective actions are required at this time. □ c. The reservoir appeared to be in fair to poor condition and requires corrective action. ☐ d. The reservoir appeared to be in unsatisfactory condition, urgent corrective action is required. Corrective Actions: ☐ e. The staff gage needs maintenance and/or repair. Description: ☐ f. A staff gage was not observed at the reservoir. Provide some method of quantifying the water level within the reservoir. g. A sinkhole was observed in the upstream reservoir. Conduct additional investigations and monitoring to identify the cause, risk and appropriate action. 4. Intake Works Description: □ Number of Intakes ☐ Intake Culvert / Pipe in. □ DIP □ Corrugated Metal □ PVC □ HDPE □ Concrete □ Other Size: Control: ☐ Gate ☐ Valve ☐ Flow can either be Shut off or Bypassed ☐ Other _ From: ☐ Stream Diversion ☐ Pump ☐ Reservoir □ Ditch / Flume Dimension: _ (Size x Depth) Shape____ ☐ Lined w/ Surface: ☐ Dirt ☐ Wood ☐ Concrete Control: ☐ Gate ☐ Valve ☐ Flow can either be Shut off or Bypassed From: ☐ Stream Diversion ☐ Pump ☐ Reservoir □ Other Findinas: x a. The intake works were not inspected. □ b. The intake works were not tested. □ c. The intake works appeared to be in satisfactory condition, no corrective actions are required at this time. □ d. The intake works appeared to be in fair to poor condition and requires corrective action. □ e. The intake works appeared to be in unsatisfactory condition, urgent corrective action is required. Corrective Actions: ☐ f. The intake works needs maintenance and/or repair. Description: _____

5.	Upstream Slope:	(Typical Slope ± <u>0.5</u> : <u>1</u>)
	Slope Protection:	x None □ Dumped Rock □ Fitted Rip Rap □ Grouted Rip Rap □ Liner □ Other:
		□ Defect in Protection: Description:
	Erosion:	□ Loose soil w/ little vegetation □ Rut (<6") x Gully (>6" deep) □ Not Visible □ None Observed
		Description: Eroded slope areas.
	Cracks:	□ Parallel with crest □ Perpendicular to crest □ Slide visible □ Not Visible □ None Observed
		Description:
	Sinkholes:	□ # Observed: Size: and Depth □ Not Visible □ None Observed
		Description:
	Vegetation:	□ None □ Low Ground Cover x Bushes or Tall Grass x Trees # □ <6" □ >6" & <20" □ >20"
		Description:
	Finalina a	
	Findings: ☐ a. The upstream	slope was not inspected.
		slope appeared to be in satisfactory condition, no corrective actions are required at this time.
	•	slope appeared to be in fair to poor condition and requires corrective action. Fixing up slope
	•	slope appeared to be in unsatisfactory condition and not expected to fulfill its intended function.
		ive action is required.
	Corrective Actions:	on needs maintenance or repair. Description: Check slope stability
		Ily erosion was observed on the slope, which requires maintenance and/or repair.
		Rut on top of crest
		bserved on the slope, which requires further investigation to determine the underlining cause. ea and/or repair as required.
	☐ h. A sinkhole was	s observed on the slope, which requires further investigation to determine the underlining cause.
	☐ i. The upstream	slope was not visible due to high grass and bush vegetation. Clear high vegetation and o enable easy visual inspection.
		observed on the dam embankment. Trees have been identified as the probably cause of piping
		an possibly cause sever damage to the embankment if they are uprooted during a high winds.
		ion is required to remove the tree hazards from the dam. Acceptable remedies include removal
		I its root structure down to a 2" diameter and reconstructing the damaged embankment section.
	An alternative	may be to trim trees as much as possible but not kill them (cut as close to the ground level). All
		all be accomplished as per the requirements of licensed geotechnical or structural engineer. itor the damaged area for signs of settlement and seepage.
		noi the damaged area for signs of settlement and seepage.

Trees getting large along slope, one area has large roots crossing over slope.

6.	6. Crest:		Approximate Crest Width: 12 feet							
		Access:	□ None x Walking Path □ Roadway, Surface / Width / Usage:							
		Erosion:	\square Loose soil w/ little vegetation \square Rut (<6") x Gully (>6" deep) \square Not Visible \square None Observed							
			Description: One gully seen on inside of crest							
		Cracks:	□ Parallel with crest □ Perpendicular to crest □ Slide visible □ Not Visible x None Observed							
			Description:							
		Sinkholes:	\square in. Wide x in. Long x in. Deep \square Not Visible x None Observed							
			Description:							
		Vegetation:	□ None □ Low Ground Cover x Bushes or Tall Grass x Trees # $\underline{100}$ □ <6" x >6" & <20" □ >20"							
			Description:							
	Find	lings:								
		_	was not inspected.							
		b. The dam crest	appeared to be in satisfactory condition, no corrective actions are required at this time.							
	Х	c. The dam crest	appeared to be in fair to poor condition and requires corrective action.							
		d. The dam crest	ne dam crest appeared to be in unsatisfactory condition and not expected to fulfill its intended function.							
		Urgent correct	ive action is required.							
	Cor	rective Actions:								
			he crest was satisfactory.							
	Х	f. Access along t	he crest was not possible. Description: Requires vegetation clearing/removal.							
		g. Rut and/or Gul Description:	ly erosion was observed on the crest, which requires maintenance and/or repair.							
			oserved on the crest, which requires further investigation to determine the underlining cause.							
		i. A sinkhole was Repair and mo	s observed on the crest, which requires further investigation to determine the underlining cause. Inition the area.							
			crest were not visible due to high grass and bush vegetation. Clear high vegetation and penable easy visual inspection.							
	x _	and can possik action is requir and its root str work shall be a	bserved along the dam crest. Trees have been identified as a probably cause of piping failures, oly cause sever damage to the embankment if they are uprooted during a high winds. Corrective ed to remove the tree hazards from the dam. Acceptable remedies include removal of the tree ucture down to a 2" diameter and reconstructing the damaged embankment section. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely maged area for signs of settlement and seepage.							

Large root crossing over crest

7 .	DOW	nstream Slope:	(Typical Slope ± <u>0.5</u> : <u>1</u>)
		Access:	☐ lower roadway along toe ☐ roadway to outlet works x walkway to outlet works ☐ None Observed
		Slope Protection:	x None ☐ Dumped Rock ☐ Rip Rap ☐ Grouted Rip Rap ☐ Concrete
		Erosion:	☐ Loose soil w/ little vegetation x Rut (<6") x Gully (>6" deep) ☐ Not Visible ☐ None Observed
			Description:spotty gullies, mostly ruts. One point was vertical
		Cracks:	□ Parallel with crest □ Perpendicular to crest □ Slide visible □ Not Visible x None Observed
			Description:
		Sinkholes:	□ in. Wide x in. Long x in. Deep □ Not Visible x None Observed
		Cirilla iono	Description:
		Vegetation:	□ None □ Low Ground Cover x Bushes or Tall Grass x Trees # □ <6" □ >6" & <20" □ >20"
		vegetation.	
		Seepage:	Description: small trees all along down slope
		Seepage.	Seep Spot Number 1 ☐ Green Vegetation ☐ Wet or Muddy Ground ☐ Ponding Water x Not Visible ☐ None Observed
			☐ Flowing, Description:
			Water Clarity: ☐ Clear ☐ Some particles ☐ Muddy ☐ Other:
			Description:
			Seep Spot Number 2
			☐ Green Vegetation ☐ Wet or Muddy Ground ☐ Ponding Water ☐ Not Visible ☐ None Observed
			☐ Flowing, Description:
			Water Clarity: ☐ Clear ☐ Some particles ☐ Muddy ☐ Other:
			Description:
,	Find	lings:	
		a. The downstrea	am slope was not inspected.
			am slope appeared to be in satisfactory condition, no corrective actions are required at this time.
	Х	c. The downstrea	am slope appeared to be in fair to poor condition and requires corrective action.
			am slope appeared to be in unsatisfactory condition and not expected to fulfill its intended
		function. Urge	ent corrective action is required.
,	Cori	rective Actions:	
	Х		on needs maintenance or repair. Description: Check slope stability
	Х		Ily erosion was observed on the slope, which requires maintenance and/or repair.
		Description:	bserved on the slope, which requires further investigation to determine the underlining cause.
			ea and/or repair as required.
			s observed on the slope, which requires further investigation to determine the underlining cause.
			onitor the area.
			am slope was not visible due to high grass and bush vegetation. Clear high vegetation and
			o enable easy visual inspection.
	Χ		observed on the downstream slope. Trees have been identified as the probably cause of piping
		CONTECTIVE ACT	an possibly cause sever damage to the embankment if they are uprooted during a high winds.
			ion is required to remove the tree hazards from the dam. Acceptable remedies include removal
		of the tree and	
		of the tree and An alternative work shall be a	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely
		of the tree and An alternative work shall be a monitor the da	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage.
		of the tree and An alternative work shall be a monitor the da h. Seepage/Pond	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal it its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage.
		of the tree and An alternative work shall be a monitor the da h. Seepage/Pond water and external	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage. Iding water was observed. Monitor and conduct further investigation to locate the source of ent of any possible hazardous or developing condition.
		of the tree and An alternative work shall be a monitor the da h. Seepage/Pond water and exter i. Seepage was	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage. ding water was observed. Monitor and conduct further investigation to locate the source of ent of any possible hazardous or developing condition. observed flowing and particles were observed to be removed by the flow. Take immediate
		of the tree and An alternative work shall be a monitor the da h. Seepage/Pono water and exte i. Seepage was action to stop to	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage. Iding water was observed. Monitor and conduct further investigation to locate the source of ent of any possible hazardous or developing condition.
		of the tree and An alternative work shall be a monitor the da h. Seepage/Pond water and exte i. Seepage was action to stop t cause and take	ion is required to remove the tree hazards from the dam. Acceptable remedies include removal its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to leave the larger trees, trim them as close to the ground without killing them. All repair accomplished as per the requirements of licensed geotechnical or structural engineer. Routinely imaged area for signs of settlement and seepage. ding water was observed. Monitor and conduct further investigation to locate the source of ent of any possible hazardous or developing condition. observed flowing and particles were observed to be removed by the flow. Take immediate the loss of soil from the embankment. Conduct further investigation to determine the underlining

8.	Abu		ents/Toe: osion:	□ Loose soil w/ little vegetation □ Rut (<6") □ Gully (>6" deep) x Not Visible □ None Observed
				Description:
		Cr	acks:	☐ Parallel with crest ☐ Perpendicular to crest ☐ Slide visible x Not Visible ☐ None Observed
		\/c	getation:	Description: □ None □ Low Ground Cover □ Bushes or Tall Grass □ Trees # □ <6" □ >6" & <20" □ >20"
		٧٥	getation.	□ None □ Low Ground Cover □ Bushes or Tall Grass □ Trees # □ <6" □ >6" & <20" □ >
		Se	epage:	Seep Spot Number 1
			1 3	☐ Green Vegetation ☐ Wet or Muddy Ground ☐ Ponding Water x Not Visible ☐ None Observed
				☐ Flowing, Description:
				Water Clarity: ☐ Clear ☐ Some particles ☐ Muddy ☐ Other:
				Description:
				Seep Spot Number 2
				☐ Green Vegetation ☐ Wet or Muddy Ground ☐ Ponding Water x Not Visible ☐ None Observed
				☐ Flowing, Description:
				Description:
	Find	-		ts/toe were not inspected.
				s/toe appeared to be in satisfactory condition, no corrective actions are required at this time.
	X			s/toe appeared to be in fair to poor condition and requires corrective action.
				s/toe appeared to be in unsatisfactory condition and not expected to fulfill its intended function.
		-		tive action is required.
	Cor	roo	tive Actions:	
				on needs maintenance or repair. Description:
				Illy erosion was observed, which requires maintenance and/or repair.
		g.		observed along the abutments/near the toe, which requires further investigation to determine the
		h	_	huse. Monitor the area and/or repair as required. I/toe area was not visible due to high grass and bush vegetation. Clear high vegetation and
				to enable easy visual inspection.
	Х	i.		observed along the abutment/toe. Trees have been identified as the probably cause of piping
				can possibly cause sever damage to the embankment if they are uprooted during a high winds.
				tion is required to remove the tree hazards from the dam. Acceptable remedies include removal
				d its root structure down to a 2" diameter and reconstructing the damaged embankment section. may be to trim trees as close to the ground without killing them. All repair work shall be
				as per the requirements of licensed geotechnical or structural engineer. Routinely monitor the
				a for signs of settlement and seepage.
		j.		ding water was observed. Monitor and conduct further investigation to locate the source of
	П	k		ent of any possible hazardous or developing condition. observed flowing and particles were observed to be removed by the flow. Take immediate
	Ш	٨.		the loss of soil from the embankment. Conduct further investigation to determine the underlining
				the corrective action. Monitor the area.
		l.		

9.	Out		Vorks: Ivert / Pipe						
		Cu	Type / Size:	24" nate	valve, cut rock				
			Culvert:	□ Concrete	☐ Masonry	x unlined earth	□ Other		
			Pipe:	□ DIP	☐ Corrugated Metal	□ PVC □ HDPI			Can't see, underwater.
			Control Type:		•	r		× • • • • • • • • • • • • • • • • • • •	Carrie Goog and an activation
			Location:			rol on Downstream s			
			Seepage:	☐ Green Vege	· etation ☐ Wet or Mud	ddy Ground x Pondi	ng Water x Not Visi	ble □Non	ne Observed
				☐ Flowing, De	escription: Through	the downstream	channel berms.		
				Water Clarity:	☐ Clear ☐ Some parti	cles x Muddy	☐ Other:		
				Description: _					
		ding		ka wara nat	inapacted				
			The outlet wor The outlet wor		•				
					tested. I to be in satisfactory	condition no co	rrective actions a	are required	l at this time
	X				I to be in fair to poor				at tino timo.
				• • •	to be in unsatisfact		•		ended function.
			Urgent correct			,	, , , , , , , , , , , , , , , , , , , ,		
	Cor	roci	ive Actions:						
				ding water w	as observed. Condu	ıct further investi	gation to locate t	he source c	of water and extent
					or developing condi		ganori to locato t	110 000100 0	water and extern
					wing and particles w				
					oil. Conduct further				
					the area. Failures c ed to be a dangerou		ge/piping along tr	ne outlet cor	nduit are very
					h grass and bush ve		nigh vegetation a	and maintair	n low to enable
	_		easy visual ins		grand and a some	9			
					the dam embankme				
			failures, and c	an possibly o	cause sever damage	to the embankm	nent if they are up	prooted duri	ing a high winds.
					ed to remove the tree cture down to a 2" d				
					complished as per th				
					aged area for signs				J
		j.							

Channel berm downstream of the outlet was being overtopped. Decrease flow into channel or fill berm low spots.

10. Spi	illway:										
	Type:	□ None □ Culvert/Pipe x	Channel								
		Description: Gate removed, portions of concrete demolished.									
	Dimension:	<u>~15</u> ft.	Invert elevation	n:ft.	per staff gage						
	Slope Protection:	□ None □ Grass □ [Dumped Rock D	∃ Fitted Rip Rap	☐ Grouted Rip Rap	x Concrete					
		☐ Defect in Protection: Desc	cription:								
	Approach:	☐ Clear x High Veg. ☐ ☐	Trees [∃Other:							
	Erosion:	☐ Scour ☐ Gully ☐ H			•						
		Description:									
	Vegetation:	□ None □ Low Ground C	over x Bushes or	Tall Grass ☐ Trees	#	□ >6" & <20" □ >20"					
-	<i></i>	Description:									
	<i>lings:</i> a The Snillway a	ppeared to be in satisfa	ctory condition	no corrective activ	ons are required a	t this time					
X	• •	ppeared to be in fair to	•		•	t tills tille.					
	• •	ppeared to be in unsatis	•	•		ded function. Urgent					
_	corrective action		oraciony contains	m and not expecte	a to railli no ilitori	aca ranction. Organi					
_		•									
	rective Actions:	on nooda maintananaa a	er ropoir Docor	intion:							
∐ X		on needs maintenance or repair. Description:									
_	Description:										
		s observed downstream of the spillway. Corrective / mitigative action is required to prevent this									
	problem from moving upstream.										
	h. Trees are unacceptable in the spillway channel and approach. Take corrective action to address the woody vegetation problem and repair the damaged area.										
х	i. Unclear if spillway is adequately sized. Spillway should pass the probable maximum flood. Verify spillway										
	capacity and to	ake corrective action as	required.								
	j										
11. Do	wn Stream Chani	nel:									
	Name: _										
	Downstream:	Sump □ Open Area □ U	n-Defined Drainage	-way ☐ Defined Dra	inage-way □ Other _						
	Items along Strea	m Bank: □ None □ Re	oad 🗆 Houses	s □ Town	x Not Insp	ected					
	Description: Cou	dn't access due to heav	y vegetation								
	lings:		()								
X		m channel was not insp		n, condition no oc	rractiva actiona o	ro required at this					
	time.	m channel appeared to	be in salistacio	ry condition, no co	medive adions a	re required at this					
		m channel appeared to	be in fair to poo	or condition and re	quires corrective a	action.					
		m channel appeared to	•		•						
		nt corrective action is re		-	·						
Cori	rective Actions:										
	e										

Additional Comments:
Findings:
On the date of this limited visual inspection, there appeared to be no immediate threat to the safety of the dam. No assurance can be made regarding the dam's condition after this date. Subsequent adverse weather and other factors may affect the dam's condition.
Heavy vegetation hampered detailed investigation. Slope angle of dam components should be analyzed for stability.
Recommendations: Immediate: Clean spillway of vegetation/siltation and keep it cleared at all times to retain full capacity. Bottom elevation of spillway approach needs to be determined. Decrease flow into the outlet works, monitor for overtopping/piping of downstream channel berms. Short-term: Clear vegetation at bottom of downstream toe and embankment (where dam meets original ground). Both should be minimum 10 feet wide to help in monitoring.
Long-term: Clear all underbrush. Trim trees as close to the ground without killing them. Fill in low spots on the crest. Do detailed investigations/studies.

Limitations and Intent of this Dam Safety Inspection:

This Dam Safety Inspection was conducted to assess the general overall condition of the reservoir/dam, identify visible deficiencies, and recommend areas of for monitoring, additional investigative studies and corrective actions. The inspection is based only on visible features/areas of the dam on the day of inspection. This inspection is not a formal phase I or phase II dam safety inspection and does not include a review or evaluation from each specialist of an inspection team, such as a geologists, civil, geotechnical, structural, or hydraulics engineer. The owner should verify the findings of this report and take corrective actions. The owner may submit to the State alternative corrective actions that are certified by a licensed professional engineer in the State of Hawaii experienced in the design and construction of dams. This inspection does not relieve the owner/operator from their responsibility to conduct routine inspections, maintenance, repairs, modifications, monitoring, documentation, and/or investigative studies. The inspection was conducted under

the authority of the Hawaii Revised Statures Chapter 179D, and Hawaii Administrative Rules, Title 13, Chapter 190, titled "Dams and Reservoirs". Questions regarding this inspection should be forwarded to the Hawaii State Dam Safety Program; PO Box 373; Honolulu, Hawaii 96809; Ph. (808) 587-0236.



